

SINGLE MERGER



2114



OXBO 2114

DELIVERING THE HIGHEST QUALITY FORAGE

Oxbo mergers have been leading the industry for over 20 years. The Oxbo 2114 single merger was designed to give smaller producers the same benefits and features of the triple mergers, **better windrows** and **better feed quality**, in a smaller, less expensive merger.

Merging your forage with the Oxbo 2114 helps deliver **lower ash content and less leaf loss**, for higher nutrition translating into more milk per cow. Hay dries faster than traditional windrows, giving more weather control to make hay-in-a-day. Plus, merging with an Oxbo creates smooth windrows without roping.

The full-width, 14-foot pick up of the Oxbo 2114 can discharge left or right and can pick up in any direction--no need to follow the windrow and restrict crop pick up.

With a self-contained PTO driven hydraulic system, you can run your 2114 with as little as a 70hp tractor.

The single Oxbo 2114 merger allows **every grower to benefit from Oxbo's unstoppable PowerMerge technology**.



Smooth windrows translate into **reduced chopper fuel consumption, faster chopper speeds**, and even knife wear.



Oxbo customers average **30% lower cost per acre** when running an Oxbo merger



PowerMerge technology translates into **the fastest merging speeds**, even in high tonnage crops.



Merging has proved to deliver the **highest feed quality** through lower ash content.

✓ EASY OPERATION

Rubber-mounted split tines are gentle on the crop and pick up less rocks and dirt than standard tines. Proven to reduce damage, deliver **cleaner product and provide longer life**.

Simple and easy to use conveyor control mounts in the tractor cab. The skid shoe system allows the 2114 to float lightly over the ground.



✓ BUILT FOR PRODUCTIVITY

40-inch wide conveyor handles heavy crop while the **optimized cam design eliminates** crop rolling in front of the pick up and retains more leaf.

Center swing chassis can swing and discharge to the left or right depending on your needs.

Powerful motors provide higher torque at the heads and conveyors to easily handle heavy crop.



SPECIFICATIONS

	Oxbo 2114
Dimesions	
Transport width	14ft 6in (4.4m)
Working width	20ft (6.10m)
Actual width	14ft 6in (4.4m)
Overall length	24ft 10in (7.6m)
Working height	7ft 4in (2.2m)
Pickup	
Conveyor length	14ft (4.27m)
Conveyor belt width	40in (1.0m)
Strippers	Poly
Rubber mounted teeth	Split tines with 2 inch spacing
Tractor Requirements	
Tractor size	70hp (52kW) or more
3-point hitch	Category II, III, or III-N
PTO	540 RPM or 1000 RPM PTO
Tractor remote couplers	2 pairs required, open or closed center
General	
Oil resevoir capacity	27 gal (102L)
Pump drive gearbox capacity	18oz (0.53L)
Maximum transport speed	20mph 932.2 km/hr)
Operating speed	2-12mph
Tire size	11L - 15 Farm/Implement - 1



Visit our website
oxbo.com