

MULTI-CROP HARVESTER



2530



Oxbo introduces the next generation in Oxbo harvesters. A John Deere ST5 engine powers the new Oxbo 2530, multi-crop harvester. It's predecessor models had a global reach spanning 6 continents and the 2530 builds upon those capabilities. The 2530 is the most trusted harvester in the world due to a fundamentally sound design, serviceability, reliability and heritage.

PERFORMANCE WHEN IT COUNTS

- Four-wheel mechanical drive chassis
- Dump box constructed of heavy-duty steel frame sections with optional conveyor to meter product discharge
- Infinitely variable hydrostatic drive motor mated to mechanical transmission for precise speed control

MULTI-HARVESTING CAPABILITIES

- Ideal for dedicated single-crop or multi-crop growers
- Can effectively harvest green beans, sugar snap peas, sweet corn, seed corn and other green crops
- · Stalk ejectors available for corn applications

PRODUCTIVITY

- Advanced monitoring and diagnostics system
- Ergonomic joystick puts all functions at operator's fingertips and user-friendly controls easily adjust to optimize yields
- · Rapid unload at any height
- Narrow design for easy trailer transport with minimal regulatory restrictions
- Industry standard for green bean cleaning and recovery with efficient airflow design
- · Easy access DEF filling space

The new Oxbo 2530 continues to carry the features you know and trust, with new technology options and an updated engine, controls and monitoring.

The 2530 may be compact, but this flexible and powerful harvester can easily adapt to a variety of crops and field conditions.

2530 FEATURES

MULTIPLE HEAD OPTIONS

The Oxbo 2530 has the flexibility to utilize multiple harvesting heads to suite your crop.

The 2530 pairs with Oxbo VPC heads for green beans and specialty crops, the Oxbo CP400 for fresh market sweet corn, Oxbo 60 series and 3000 series heads for processing sweet corn and seed corn and the POG SP heads for spinach and greens.





EASY ACCESS LADDER

New design for operating mode. Simply flip locking lever up and pull ladder out of the way.



DUAL CLEANING FANS

Powerful fans are easily set from within the cab for the cleanest loads



COMFORTABLE CAB

Climate controlled operator station with integrated controls provides outstanding visibility



ARTICULATING CHASSIS

Rear wheels track with front wheels for easier, more responsive steering for sharp turns and handling rough field conditions

SPECIFICATIONS

Dimensions (with standard tire)		
Length without header	27 ft 3 in (8.31 m)	
Width without header	8 ft 4 in (2.54 m)	
Height	13 ft 1 in (3.99 m)	
Wheelbase	10 ft 12 in (3.34 m)	
Track Width (wheel center lines)	6 ft 4 in (1.93 m)	
Inside turning radius	15 ft 4 in (4.67 m)	
Weight without header	26,280 lbs (11,920 kg)	
Tires		
Standard 23.1 x 26	Titan High Traction Lug 16 ply Bias	
Engine	EU Stage V	Tier 3 (available for export only)
Engine model	John Deere 6068 T4/Stage V	John Deere 6068 T3
Horsepower	173 hp (129 kW) @ 2200 rpm	173 hp (129 kW) @ 2200 rpm
Tank Capacities	EU Stage V	Tier 3 (available for export only)
Fuel	160 gal (605.7 L)	160 gal (605.7 L)
DEF	9.1 gal (34.4 L)	NA
Hydraulic reservoir	68gal (257.4 L)	68gal (257.4 L)
Cooling system	6 gal (27.3 L)	6.25 gal (28.4 L)
Crankcase	5 gal (18.9 L)	5 gal (18.9 L)
Dump Box		
Volume	390 ft ³ (11.04 m ³)	
Dump box lifting capacity	10,000 lbs (4,545 kg)	
Dump height to dump box lip	8 ft 1 in - 14 ft 4 in (2.46 m - 4.36 m) without extension	
Dump angle	46 degrees from horizontal	
Dump reach (with standard tire)	35 in (0.89 m) without extension 44 in (1.12 m) with extension	
Harvesting Head Capabilities		
Beans, Hemp, Stevia	Oxbo VPC II 1200 - 120 in (3.05 m) width Oxbo VPC II 1500 - 150 in (3.81 m) width Oxbo VPC II 1800 - 180 in (4.57 m) width	
Fresh Market Sweet Corn	Oxbo CP400 (4 rows)	
Seed & Processed Sweet Corn	Oxbo 3000 & 60 Series (6 row max)	
Spinach & Greens	Oxbo SP3500 - 138 in (3.5 m) width Oxbo SP4500 - 177 in (4.5 m) width	



Oxbo International 100 Bean Street Clear Lake, WI 54005 Visit our website at **oxbo.com**



800.628.6196