

CORN HARVESTER



8530



8530

The Oxbo 8400 series multi-crop harvesters have been the industry standard for sweet corn and seed corn harvesting globally for decades. The next generation Oxbo 8530 has many new improvements including a Tier 4 engine to comply with global emission standards. Meet the new and improved 8530!

NEW SCANIA ENGINE

- New Scania Tier 4F 9.3L engine provides dramatically increased fuel economy
- Low DEF consumption
- 375 hp engine has more power and torque with a significant reduction in noise levels
- Standard one year manufacturer warranty with multiple extended warranty options

STANDARD FEATURES

- Your choice of belted or chain feeder house and incline conveyor capable of operating a 14 row head
- Can harvest both sweet corn and seed corn
- Spacious cab with panoramic view

OPTIONAL FEATURES

- Optional LED lighting offers the brightest view for night time harvesting operations
- Multiple wheel configurations for single or dual front wheels and tire track spacings
- Belt or chain cleaning system
 - Choice of either belted or chained elevators in a variety of lengths
- PRECISION PACKAGES
 - YieldTracker maps variable yield data for agronomic analysis
 - Steer-By-Stalk to ensure better on-row performance and reduce operator stress

Oxbo continues to research and develop innovative ways to make your job easier and more efficient. With every machine we design, our central goal has always been, and will continue to be, to help our customer become more profitable.

At Oxbo, we are committed to optimizing farming together.

8530 FEATURES

The 8530 offers a wide array of features and options built around your productivity.

Each feature was designed for high quality crop and reliable in-field performance. Trusted for decades, the 8530 builds on Oxbo's tradition of performance and offers a full range of engine options to meet various global emission requirements.



POWER, ACCESS, & CONVENIENCE

- Powerful 9.3L Scania Tier IV engine delivers unmatched fuel economy and powers through all field and crop conditions
- New engine compartment design allows for easier access for quick and easy routine engine maintenance
- Centralized cabinet with easy access to filters, valves, and power supply making service tasks faster and more convenient



CUSTOMIZE FOR YOUR FIELD, YOUR CONDITIONS

- Select the optional belted elevator to gently convey valuable crops
- Fully customized performance with a wide range of track width settings. Combined with extensive tire choice, the 8530 is designed to meet your field conditions
- Add extra wide catwalks, various elevator design and belt or chain conveyance to match your fleet or to improve in-field performance



CONSISTENTLY CLEAN CROP

- Powerful fans remove trash enabling the 8530 to deliver clean loads
- Choose your cleaning system. Pick between the proven, reliable performance of the 601 chain cleaning unit or the gentle handling and improved conveyance of the belted 602 cleaning unit

SPECIFICATIONS

Standard Specifications	
Transport dimensions	
Length (machine only):	28ft 3in (8.6m)
Width (without header):	11ft 3in (3.43m)
Height:	13ft 1in (3.99m)
Wheelbase:	13ft 8in (4.17m)
Width of wheel centers model 8530C:	101 in (2.57m)
Width of wheel centers model 8530W:	120 in (3.05m)
Width of wheel centers model 8530CW:	90 in and 120 in (rear) (2.29m/3.05m)
Width of wheel centers model 8530CWE:	120 in and 150 in (rear) (3.05m/3.81m)
Tires	
Front tire options 8530C & 8530W:	800/65R32 or 900/60R32 Michelin MEGAXBIB
Rear tire options 8530C & 8530W:	480/80R26 Michelin XMCL Industrial
	VF520/80R26 Michelin CEREXBIB
	600/65R28 Firestone All-traction DT
Front tire options 8530CW & 8530CWE:	620/70R42 Firestone All-traction DT
	520/85R42 Michelin AGRIBIB
	650/65R42 Goodyear DT820 TL
Rear tire options 8530CW & 8530CWE:	600/65R28 Firestone All-traction DT
	480/80R26 Michelin XMCL Industrial
	VF520/80R26 Michelin CEREXBIB
Engine	
Engine:	Scania 9.3L Tier 4F/EU STG V V (stgV has same power ratings)
Horsepower:	375hp @ 1850 rpm (275.8kW) [Scania publishes - 375hp (276kW)]
Tier 3 engine (Available for export only)	John Deere 9L
Tier 3 horsepower	350hp @ 2200 rpm (257.4kw) [Deere publishes - 350hp (261kW)]
Ground Speeds	
4 wheel drive (Lo):	6.5mph (10.5 km/hr)
4 wheel drive (High):	14 mph (22.5 km/hr)
2 wheel drive (Lo):	10.5mph (16.9 km/hr)
2 wheel drive (High):	21mph (33.8 km/hr)
Tank Capacities	
Fuel: (T4F & EU STG V) (stgV has same capacities)	250 gallons (946.4L)
Engine oil system capacity:	9.5 gallons (36L)
Diesel exhaust fluid (DEF):	10 gallons (37.9L)
Hydraulic fluid:	70 gallons (265L)
Cooling system:	20 gallons (75.7L)
Fuel: (Tier 3)	250 gallons (946.4L)
Engine oil system capacity: (Tier 3)	8 gallons (30.3L)
Hydraulic fluid: (Tier 3)	70 gallons (265L)
Cooling system: (Tier 3)	15 gallons (56.8L)



Oxbo International
100 Bean Street
Clear Lake, WI 54005

Visit our website at
oxbo.com



715.263.2112

800.628.6196